



245 (12 Ton) 6 Wheel Model

- 12 ton tandem wagon gear
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8' 8" - 11' 2"
- Safety chain (3/8" GR. 70)

Specifications

Capacity (30 kph / 20 mph)	24,000 lb
Capacity (50 kph / 30 mph)	24,000 lb
Spindles (Front)	2-3/4" Dia. C1045 Cold Rolled
Spindles (Rear)	2-1/4" Dia. C1045 Cold Rolled
Hubs	6 Bolt
Bearings - Bore Size (Inner/Outer)	Taper Roller 1.80/1.38
Front Axle	6 x 3 x .250 Wall
Rear Axle	6 x 3 x .250 Wall
Tongue Bracket Mounting	1-1/2" Bolt Bearing Mtd.
Tongue Bolt	1-1/8" Dia.
Tongue Latch	Retractable Automatic Relock
Reach Poles	3" O.D. x .188 Wall - Round Tube
Bolster Stakes	Adjustable 38.5" - 40.5" - 42.5"
Steering	Automotive Type
Tie Rod Ends	Greasable Automotive Style Ball Joints
Wheel Base	Adjustable
Height from Ground to Top of Bunk	23" on 11L x 15 Tires
Approx. Weight	985 lbs. (less rims and tires)

Options

Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'
Narrow track (Custom Build) down to 60"
Wide Track (Custom Build) up to 90"
Wide Track (Custom Build) over 90"
Single spring balancer
Double spring balancer
Rocking bolster
Rocking bolster for ammonia tank
4" bolt on riser kit (other heights available)

Rim & Tire Sizes

11L x 15	8 Ply	15 x 8 x 6	76"	15,240
225/75 R15	D Range	15 x 6 x 6	76"	15,240
12.5L x 15	12 Ply	15 x 10 x 6	78"	21,840
12.5L x 16	14 Ply	16 x 10 x 6	75"	24,000
245 R16	Used Truck / New Tubes	16 x 8 x 6	76"	21,000
11L x 15	D Range / Hwy Ser.	15 x 8 x 6 HD	76"	18,720
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	76"	23,760

Capacities listed are max tire capacity. See wagon specifications for maximum wagon capacity.

<https://horstwagons.com/wagons/running/245.php> **1.866.567.4162**