



# 265 (14 Ton) 6 Wheel Model

- 14 ton tandem wagon gear
- Quick hitch tongue
- Standard reach length 11'
- Wheel Base adjustable 8' 8" - 11' 2"
- Safety chain (1/2" GR. 70)

## Specifications

Capacity (30 kph / 20 mph)	28,000 lb
Capacity (50 kph / 30 mph)	27,000 lb
Spindles	2-1/4" Dia. C1045 Cold Rolled
Hubs	8 Bolt
Bearings - Bore Size (Inner/Outer)	Taper Roller 1.80/1.38
Front Axle	7 x 3 x .250 Wall
Rear Axle	7 x 3 x .313 Wall
Tongue Bracket Mounting	1-1/2" Bolt Bearing Mtd.
Tongue Bolt	1-1/8" Dia.
Tongue Latch	Retractable Automatic Relock
Reach Poles	3" O.D. x .188 Wall - Round Tube
Bolster Stakes	42.5" Fixed
Steering	Automotive Type
Tie Rod Ends	Greasable Automotive Style Ball Joints
Wheel Base	Adjustable
Height from Ground to Top of Bunk	26" (12.5 x 16 Tires) 30" (11 x 22.5 Tires)
Approx. Weight	1,155 lbs. (less rims and tires)

## Options

Optional Reach Lengths: 9', 11', 12', 14', 16', 18', 20', 22'

<b>Add or subtract price per foot for over or under 11' (includes both reach poles)</b>
<b>Narrow track (Custom Build) down to 60"</b>
<b>Wide Track (Custom Build) up to 90"</b>
<b>2 wheel free backing surge brakes c/w double spring balancer (includes brake tongue)</b>
<b>4 wheel surge brakes</b>
<b>Single spring balancer</b>
<b>Double spring balancer</b>
<b>Rocking bolster</b>
<b>Rocking bolster for ammonia tank</b>
<b>4" bolt on riser kit (other heights available)</b>

## Rim & Tire Sizes

<b>12.5L x 15</b>	12 Ply	15 x 10 x 8	82"	21,840
<b>12.5L x 16</b>	14 Ply	16 x 10 x 8	82"	25,080
<b>12.5L x 15</b>	F Range / Hwy Ser.	15 x 10 x 8 HD	82"	28,000
<b>14L x 16.1</b>	8 Ply	16.1 x W11C x 8	82"	23,160
<b>14L x 16.1</b>	12 Ply	16.1 x W11C x 8	82"	28,000

Capacities listed are max tire capacity. See wagon specifications for maximum wagon capacity.