



365E (20 Ton) 4 Wheel Economy Model

- 20 ton HD wagon gear
- Quick hitch tongue
- Standard reach length 10'
- Wheel base adjustable 10' 7" - 12' 1"
- Disc brake flanges
- Safety chain (1/2" GR. 70)

Specifications

Capacity (30 kph / 20 mph)	40,000 lb
Capacity (50 kph / 30 mph)	36,000 lb
Spindles	3" Diameter, 1144 Stress Proof
Hubs	8 Stud
Front Axle	10 x 4 x .250 Wall
Rear Axle	10 x 4 x .188 Wall
Tongue Bracket Mounting	1-1/2" Bolt Bearing Mtd.
Tongue Bolt	1-1/8" Diameter
Bolster	Flexible Front
Reach Tubes	6 x 4 x .188 Tubes
Bolster Stakes	42.5" Fixed
Steering	Automotive Type
Tie Rod Ends	Greasable Automotive Style Ball Joints
Wheel Base	Adjustable
Height From Ground To Top of Bunk	34" on 18 x 22.5 Tires
Approx. Weight	1,495 lbs. (less rims and tires)

Options

Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'

Narrow track (Custom Build) down to 60"

Wide Track (Custom Build) up to 90"

Wide Track (Custom Build) over 90"

2 Wheel HD hydraulic disc brakes (remote) must use 22.5 rim**

Single spring balancer

Double spring balancer

4" bolt on riser kit (other heights available)

**Hydraulic brake system also works on a brake pedal outlet kit.

Rim & Tire Sizes

16.5 x 16.1	10 Ply	16.1 x W14C x 8	93"	20,800
19L x 16.1	12 Ply	16.1 x W16C x 8	95"	24,000
21.5 x 16.1	14 Ply	16.1 x W16C x 8	95"	31,400
425 x 22.5	Used Truck	22.5 x 13 x 8	86"	40,000
425 x 22.5	New Recap	22.5 x 13 x 8	86"	40,000
425 x 22.5	New Truck	22.5 x 13 x 8	86"	40,000
445/50 x 22.5	New Recap	22.5 x 13 x 8	86"	40,000
445 x 22.5	New Truck	22.5 x 13 x 8	86"	40,000
400 / 55 x 22.5	16 Ply	22.5 x 13 x 8	86"	31,280
560 / 45 x 22.5	16 Ply	22.5 x 16 x 8	92"	38,560

Capacities listed are max tire capacity. See wagon specifications for maximum wagon capacity.

<https://horstwagons.com/wagons/running/365E.php> **1.866.567.4162**