



## 605 (30 Ton) 6 Wheel Model

- 30 ton HD tandem wagon gear
- Quick hitch tongue
- Rocking Bolster
- Standard reach length 10'
- Wheel base adjustable 10' 7" - 12' 1"
- Disc brake flanges
- Safety chain (5/8" GR. 70)

### Specifications

<b>Capacity (30 kph / 20 mph)</b>	60,000 lb
<b>Capacity (50 kph / 30 mph)</b>	60,000 lb
<b>Spindles</b>	4" Dia. C1045 Cold Rolled
<b>Hubs</b>	10 Stud
<b>Front Axle</b>	10 x 4 x .500 Wall
<b>Rear Axle</b>	10 x 4 x .500 Wall
<b>Tongue Bracket Mounting</b>	1-1/2" Bolt Bearing Mtd.
<b>Tongue Bolt</b>	1-1/2" Dia.
<b>Reach Tubes</b>	6 x 4 x .188 Tubes
<b>Bolster Stakes</b>	42.5" Fixed
<b>Steering</b>	Automotive Type
<b>Tie Rod Ends</b>	Greasable Automotive Style Ball Joints
<b>Wheel Base</b>	Adjustable
<b>Height from Ground to Top of Bunk</b>	34" on 18 x 22.5 Tires
<b>Approx. Weight</b>	3,295 lbs. (less rims and tires)

### Options

Optional Reach Lengths: 8', 10', 12', 14', 16', 18', 20'

**Narrow track (Custom Build) down to 60"**

**4 Wheel HD hydraulic disc brakes (remote)\*\***

**2 Wheel HD hydraulic disc brakes (remote)\*\***

**Double spring balancer**

**4" bolt on riser kit (other heights available)**

\*\*Hydraulic brake system also works on a brake pedal outlet kit.

## Rim & Tire Sizes

<b>425 x 22.5</b>	Used Truck	22.5 x 13 x 10	86"	60,000
<b>425 x 22.5</b>	New Recap	22.5 x 13 x 10	86"	60,000
<b>425 x 22.5</b>	New Truck	22.5 x 13 x 10	86"	60,000
<b>445 x 22.5</b>	Used Truck	22.5 x 13 x 10	86"	60,000
<b>445/50 x 22.5</b>	New Recap	22.5 x 13 x 10	86"	60,000
<b>445 x 22.5</b>	New Truck	22.5 x 13 x 10	86"	60,000
<b>400 / 55 x 22.5</b>	16 Ply	22.5 x 13 x 10	86"	46,920
<b>560 / 45 x 22.5</b>	16 Ply	22.5 x 16 x 10	92"	57,840

Capacities listed are max tire capacity. See wagon specifications for maximum wagon capacity.

<https://horstwagons.com/wagons/running/605.php> **1.866.567.4162**