

145 (8 Ton) 4 Wheel Model

- 8 ton wagon gear
- · Quick hitch tongue
- Standard reach length 6' 7"
- Wheel Base adjustable 7'-11'
- Safety chain (3/8" GR. 70)

Specifications

Capacity (30 kph / 20 mph)	16,000 lb		
Capacity (50 kph / 30 mph)	12,000 lb		
Spindles	1-3/4" Diameter, C1045 Hot Rolled		
Hubs	6 Bolt		
Bearings - Bore Size (Inner/Outer)	Taper Roller (1.50 / 1.25)		
Front Axle	5.5 x 3 x .188 Wall		
Rear Axle	5.5 x 3 x .188 Wall		
Tongue Bracket Mounting	1-1/2" Bolt Bearing Mtd.		
Tongue Bolt	7/8" Diameter		
Tongue Latch	Retractable Automatic Relock		
Reach Poles	3" O.D. x .188 Wall - Round Tube		
Bolster Stakes	Adjustable 38.5" - 40.5" - 42.5"		
Steering	Automotive Type		
Tie Rod Ends	Greasable Automotive Style Ball Joints		
Wheel Base	Adjustable		
Height From Ground To Top of Bunk	24" (on 11L x 15 Tires)		
Approx. Weight	535 lbs. (less rims and tires)		

Options

Optional 10' reach length (wheel base adj. 11' to 14')

High clearance option (6" increase - refer to specification page 50)

Narrow track (Custom Build) down to 60"

Wide track (Custom Build) up to 90"

Single Spring Balancer

4" bolt on riser kit (other heights available)

Rim & Tire Sizes

11L x 15	8 Ply	15 x 8 x 6	74"	10,160
225/75 R15	D Range	15 x 6 x 6	74"	10,160
12.5L x 15	12 Ply	15 x 10 x 6	76"	14,560
245 R16	Used Truck / New Tubes	16 x 8 x 6	74"	14,000
11L x 15	D Range / Hwy Ser.	15 x 8 x 6 HD	74"	12,480
11L x 15	F Range / Hwy Ser.	15 x 8 x 6 HD	74"	15,840
26 x 12	12 Ply	12 x 10.5 x 6	80"	11,000

Capacities listed are max tire capacity. See wagon specifications for maximum wagon capacity.

https://horstwagons.com/wagons/running/145.php 1.866.567.4162